

---



---




---



---

Tetrix Adjustable Recessed 62 1x IP55 LED 2700K Medium DE White Matt




**Specifications**

|                                 |   |      |
|---------------------------------|---|------|
| Material                        | 13517138  |      |
| Light Source Type               | LED   |      |
| LED Type                        | BRIDGELUX V8G8  |      |
| LED technology                  | LED COB   |      |
| CRI                             | Min. 90   |      |
| Colour Temperature              | 2700K   |      |
| Lifetime                        | L90B10 @50,000 Hours                                    |      |
| Lamp Included                   | Yes   |      |
| Number of Light Sources         | 1   |      |
| CIE flux code                   | 97 99 100 100 100                                       |      |
| Binning (SDCM)                  | 2   |      |
| Light Direction                 | Down  |      |
| Optic                           | Collimator  |      |
| Measured beam angle (°)         | 23.0  |      |
| Input Voltage                   | Constant Current Driver Required                        |      |
| Electrical Class                | III   |      |
| IP Rating                       | 55  |      |
| Glow wire rating (°C)           | 850   |      |
| Indoor/Outdoor                  | Indoor  |      |
| Application                     | Ceiling, Wall   |      |
| Mounting                        | Recessed  |      |
| Cut-out size (mm)               | Ø68 for Frame Recessed; Ø89 for Frame Recessed TrimLess |      |
| Mounting depth (mm)             | 110.0   |      |
| Adjustability                   | H 355° V 25°  |      |
| Distance to Lighted Object (m)  | 0,1   |      |
| Primary Colour & Primary Finish | White, Matt   |      |
| Gross weight (g)                | 141.0   |      |
| Drive current (mA)              | 350   | 500  |
| Min. forward voltage (Vf)       | 13,2  | 13,7 |
| Max. forward voltage (Vf)       | 15,0  | 15,4 |
| Connected load (W)              | 5,0   | 7,2  |
| Luminous flux per lamp (lm)     | 491   | 660  |
| Efficacy (lm/W)                 | 98  | 92   |
| Glare rating                    | 15  | 16   |


Playing with pieces, fitting them together in all kinds of intricate ways. Tetrix invites you to give it your personal touch with design options and accessories. It's versatile, fits everywhere, and is a breeze to install.


Remark

- Tetrix Recessed Ring or Tube Surface not included
- This is not a complete product. Tetrix Recessed Ring or Tube Surface required.
- This is not a complete product. Tetrix Recessed Ring or Tube Surface required.


**TM30 & CRI diagram**

**Light distribution & beam diagram**




### Optical Accessories







**13515032** Snoot 32 Black Structure

**13515038** Snoot 32 White Matt

**13515132** Honeycomb 33 Black Structure

### Installation Accessories


**13510083** Ring Recessed 62 1x IP55 Black Matt

**13510038** Ring Recessed 62 1x IP55 White Matt

**13515430** Ring Recessed Trimless 62 1x

**13515530** Concrete Kit 62 150x150 1x


**13515630** Concrete Ring 62 Standard Installation Housing

**12293230** Plaster Kit Trimless 150x150 - 62 1x

**11624030** Installation Housing 140x250x100x210

**12292630** Gypsum Fibreboard 150x150

**13515738** Tetrix Tube Surface 65 125 1x DE White Matt

**13515783** Tetrix Tube Surface 65 125 1x DE Black Matt

Choose a required accessory