


Pate	
Customer	
Project	
ype	

Sulfer Wall Up/Down 2x LED 3000K Trailing Edge DI Silver Bronze Brushed



Sulfer is a minimalistic square-shaped luminaire. The cast aluminium housing brings a modern accent to walls, whether they're in- or outside (IP54) homes, hotels, restaurants, and more. Sulfer diffuses a wide beam (flood), which can be customised by an additional beam angle plate (medium and small). A recessed light source and a diffuser ensure only indirect and soft light.





α					r.						
7	n	ρ	\mathcal{C}	71	1	\mathcal{C}	П	11	α	n	S
┙,	Μ	·	·	٠,	·	·	u	••	•	'''	$\boldsymbol{\mathcal{S}}$

Material	13270116
Light Source Type	LED
LED Type	BRIDGELUX V8G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	57 89 98 50 56
Binning (SDCM)	2
Light Direction	Up/Down
Input Voltage	230V
Luminaire power (W)	6.6
Electrical Class	1
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Wall
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Silver Bronze, Brushed
Gross weight (g)	725.0
Luminous flux per lamp (lm)	345
Efficacy (Im/W)	52
Glare rating	17




TM30 & CRI diagram






Light distribution & beam diagram






Optical Accessories



13271009 Beam Aperture Plate Sulfer Spot White Structure **13271032** Beam Aperture Plate Sulfer Spot Black Structure



13271109 Beam Aperture Plate Sulfer Medium White Structure **13271132** Beam Aperture Plate Sulfer Medium Black Structure

Choose a required accessory