


Pate
Customer
Project
уре

## Minude Track 48V Adjustable 45 2x LED 2700K Spot DALI Bronze Brushed Anodised



Minude's yogic flexibility will surprise you about as much as its bare, cylindrical design. Express a refined and minimalistic look & feel on walls, on high or low ceilings. Try more than one Minude on our Pista track or on our redesigned Modupoint LED. Its long string of colours and miniature size will make a big impression.





S	p	e	c	ij	fic.	a	ti	0	ns	5

Material	13711582					
Light Source Type	LED					
LED Type	CITIZEN CLU7A3					
LED technology	LED COB					
CRI	Min. 90					
Colour Temperature	2700K					
Lifetime	L90B10 @50,000 Hours					
Lamp Included	Yes					
Number of Light Sources	2					
CIE flux code	100 100 100 100 39					
Binning (SDCM)	2					
Light Direction	Down					
Optic	Lens					
Measured beam angle (°)	16.0					
Input Voltage	48Vdc					
Luminaire power (W)	14.5					
Electrical Class	III					
IP Rating	20					
Glow wire rating (°C)	960					
Dimming Protocol	DALI					
DALI Standard	DALI-2					
Indoor/Outdoor	Indoor					
Application	Ceiling, Wall					
Adjustability	H 360° V 0°/+90°					
Distance to Lighted Object (m)	0,1					
Primary Colour & Primary Finish	Bronze, Brushed Anodised					
Gross weight (g)	573.0					
Drive current (mA)	500					
Luminous flux per lamp (lm)	262					
Efficacy (Im/W)	47					
Glare rating	1					
Remark	<ul> <li>This is not a complete product. Pista track 48V system required.</li> <li>For installations without dimmer, it is recommended to use 1-10 V luminaires.</li> </ul>					





## TM30 & CRI diagram





## Light distribution & beam diagram

