




| |
|----------|
| Date |
| Customer |
| Project |
| Type |

Tetrix Straight Recessed 62 1x IP55 LED 2700K Spot DE White Matt



Playing with pieces, fitting them together in all kinds of intricate ways. Tetrix invites you to give it your personal touch with design options and accessories. It's versatile, fits everywhere, and is a breeze to install.





Specifications


| | |
|---------------------------------|---|
| Material | 13730038 |
| Light Source Type | LED |
| LED Type | CITIZEN CLU7A3 |
| LED technology | LED COB |
| CRI | Min. 90 |
| Colour Temperature | 2700K |
| Lifetime | L90B10 @50,000 Hours |
| Lamp Included | Yes |
| Number of Light Sources | 1 |
| CIE flux code | 99 99 100 100 98 |
| Binning (SDCM) | 2 |
| Light Direction | Down |
| Optic | Collimator |
| Measured beam angle (°) | 15.0 |
| Input Voltage | Constant Current Driver Required |
| Electrical Class | III |
| IP Rating | 55 |
| Glow wire rating (°C) | 850 |
| Indoor/Outdoor | Indoor |
| Application | Ceiling, Wall |
| Mounting | Recessed |
| Cut-out size (mm) | ø68 for Frame Recessed; ø89 for Frame Recessed TrimLess |
| Mounting depth (mm) | 110.0 |
| Adjustability | Not Applicable |
| Distance to Lighted Object (m) | 0,1 |
| Primary Colour & Primary Finish | White, Matt |
| Gross weight (g) | 146.0 |
| Drive current (mA) | 350 500 |
| Min. forward voltage (Vf) | 11,2 11,2 |
| Max. forward voltage (Vf) | 13,2 13,2 |
| Connected load (W) | 4,1 6,1 |
| Luminous flux per lamp (lm) | 399 538 |
| Efficacy (lm/W) | 97 88 |
| Glare rating | 11 12 |

Remark


- Tetrix Recessed Ring or Tube Surface not included
- This is not a complete product. Tetrix Recessed Ring or Tube Surface required.
- This is not a complete product. Tetrix Recessed Ring or Tube Surface required.

TM30 & CRI diagram

Light distribution & beam diagram


Optical Accessories




13515132 Honeycomb 33 Black Structure




13515038 Snoot 32 White Matt

13515032 Snoot 32 Black Structure



13515232 Light Cone 44 Black Structure


13515238 Light Cone 44 White Matt



13515332 Light Cone 64 Black Structure


13515338 Light Cone 64 White Matt

Installation Accessories




13510083 Ring Recessed 62 1x IP55 Black Matt


13510038 Ring Recessed 62 1x IP55 White Matt




13515430 Ring Recessed Trimless 62 1x




13515530 Concrete Kit 62 150x150 1x




13515630 Concrete Ring 62 Standard Installation Housing



12293230 Plaster Kit Trimless 150x150 - 62 1x



11624030 Installation Housing 140x250x100x210



12292630 Gypsum Fibreboard 150x150

Choose a required accessory