


Date	
Customer	
Project	
Туре	

Nude Wall Up/Down 70 2x LED PAR20 E27 2700K Medium Leading Edge/Trailing Edge Bronze Brushed Anodised



Nude's pure geometrical lines are ideal for highlighting architectural features. A long, thin, wall luminaire with indirect light, it is completely stripped down to the essence of what constitutes a luminaire. Its light source is recessed in the slender cylinder so much so that it is practically invisible. Complement the light effect with white or black, or a row of rich colours.





α					c.						
١.	\boldsymbol{n}	P.	c	7.	† 1.	C	a	Ħ	10	n	8
~	Ρ	•	_	٠,	~	•	υv	"	\sim		~

Material	10922982				
Light Source Type	LED PAR20 E27				
LED Type	NUDE PH MAS LEDSP PAR20				
LED technology	LED high power				
CRI	Min. 90				
Colour Temperature	2700K				
Lifetime	L70B50 @25,000 Hours				
Lamp Included	Yes				
Number of Light Sources	2				
CIE flux code	92 100 100 50 94				
Binning (SDCM)	3				
Light Direction	Up/Down				
Optic	Collimator				
Measured beam angle (°)	21.0				
Input Voltage	230V				
Luminaire power (W)	12.0				
Electrical Class	I				
IP Rating	20				
Dimming Protocol	Leading Edge, Trailing Edge				
Indoor/Outdoor	Indoor				
Application	Wall				
Mounting	Surface				
Distance to Lighted Object (m)	0,1				
Primary Colour & Primary Finish	Bronze, Brushed Anodised				
Gross weight (g)	1144.0				
Delivered lumens (lm)	1160				
Efficacy (Im/W)	97				
Glare rating	13				
Giare rating	13				



TM30 & CRI diagram





Light distribution & beam diagram

