

Date			
Customer			
Project			
Туре			

шe


Nude Wall Up/Down 70 2x LED PAR20 E27 2700K Medium Leading Edge/Trailing Edge Silver Bronze Brushed

Anodised

Specifications



Nude's pure geometrical lines are ideal for highlighting architectural features. A long, thin, wall luminaire with indirect light, it is completely stripped down to the essence of what constitutes a luminaire. Its light source is recessed in the slender cylinder so much so that it is practically invisible. Complement the light effect with white or black, or a row of rich colours.



Specifications


specifications		
Material	10922984	
Light Source Type	LED PAR20 E27	
LED Type	NUDE PH MAS LEDSP PAR20	
LED technology	LED high power	
CRI	Min. 90	
Colour Temperature	2700K	
Lifetime	L70B50 @25,000 Hours	
Lamp Included	Yes	
Number of Light Sources	2	
CIE flux code	91 99 100 50 95	
Binning (SDCM)	3	
Light Direction	Up/Down	
Optic	Collimator	
Measured beam angle (°)	22.0	
Input Voltage	230V	
Luminaire power (W)	12.0	
Electrical Class	1	
IP Rating	20	
Dimming Protocol	Leading Edge, Trailing Edge	
Indoor/Outdoor	Indoor	
Application	Wall	
Mounting	Surface	
Distance to Lighted Object (m)	0,1	
Primary Colour & Primary Finish	Silver Bronze, Brushed Anodised	
Gross weight (g)	1144.0	
Delivered lumens (Im)	1170	
Efficacy (Im/W)	97	
Glare rating	14	



Nude Wall Up/Down 70 2x LED PAR20 E27 2700K Medium Leading Edge/Trailing Edge Silver Bronze Brushed Anodised

TM30 & CRI diagram





Light distribution & beam diagram

