


Thimble Recessed Trimless Adjustable 70 1x LED 2700K Spot DE Gold Brushed Anodised



Specifications


| | |
|---------------------------------|----------------------------------|
| Material | 11623242 |
| Light Source Type | LED |
| LED Type | CITIZEN CLU7A3 |
| LED technology | LED COB |
| CRI | Min. 90 |
| Colour Temperature | 2700K |
| Lifetime | L90B10 @50,000 Hours |
| Lamp Included | Yes |
| Number of Light Sources | 1 |
| CIE flux code | 100 100 100 100 40 |
| Binning (SDCM) | 2 |
| Light Direction | Down |
| Optic | Lens |
| Measured beam angle (°) | 16.0 |
| Input Voltage | Constant Current Driver Required |
| Electrical Class | III |
| IP Rating | 20 |
| Glow wire rating (°C) | 960 |
| Indoor/Outdoor | Indoor |
| Application | Ceiling |
| Mounting | Recessed |
| Cut-out size (mm) | ø111 |
| Mounting depth (mm) | 110.0 |
| Adjustability | H 360° V 30° |
| Distance to Lighted Object (m) | 0,1 |
| Primary Colour & Primary Finish | Gold, Brushed Anodised |
| Gross weight (g) | 225.0 |
| Drive current (mA) | 350 500 |
| Min. forward voltage (Vf) | 11,2 11,2 |
| Max. forward voltage (Vf) | 13,2 13,2 |
| Connected load (W) | 4,1 6,1 |
| Luminous flux per lamp (lm) | 197 266 |
| Efficacy (lm/W) | 48 44 |
| Glare rating | 0 0 |

Minimalistic design, subtle curves, revealing colours, high-quality lens and LED. With its deep-recessed and glare-free light source, Thimble's clean and seamless execution makes it a quiet yet sophisticated choice for high-end residential or hospitality settings. This versatile, elegant architectural downlighter brings pure form, definition and quality light without stealing all the attention.

TM30 & CRI diagram




Light distribution & beam diagram




Installation Accessories



11624230 Concrete Kit 70 150x150 1x




11624430 Concrete Ring 70 Standard Installation Housing




11624030 Installation Housing 140x250x100x210



12292630 Gypsum Fibreboard 150x150



12293630 Plaster Kit Trimless 150x150 - 70 1x



■ **11624730** Ring Recessed Trimless 70 1x

■ Choose a required accessory