

Date
Customer
Project
Туре



An abstract square shape that transforms into a poem of light and shadow. Impulse Square Wall brings a surprising light effect to any surface it touches.

25 165 80 <sup></sup>	Frends of Received
pecifications	
aterial	13770836


Specifications	
Material	13770836
Light Source Type	LED
LED Type	LED PCB IMPULSE
LED technology	LED PCB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	0 8 38 5 88
Binning (SDCM)	3
Light Direction	Up, Down
Measured beam angle (°)	120.0
Input Voltage	230V
Luminaire power (W)	7.5
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Wall
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Grey White, Structure
Gross weight (g)	864.0
Delivered lumens (Im)	561
Efficacy (Im/W)	75
Glare rating	26

## Impulse Square Wall 1x LED 2700K Trailing Edge DI Grey White Structure



## TM30 & CRI diagram





## Light distribution & beam diagram

