


Pate
Customer
Project
уре

Chival Wall Up/Down 292 2x LED 2700K Trailing Edge DI Black Chrome



Formed by one single, pleated plate, Chival shows elements of sharp design and refined craftsmanship. Its up and down vertical light is a natural continuation of the shape, which was inspired by medieval coats of arms. Alone, Chival is beautiful and timeless. Try two or more, and you'll see a conversation of shadow, light and patterns taking shape.





Specifications		
	Material	13760080
	Light Source Type	LED
	LED Type	CREE 1304
	LED technology	LED COB
	CRI	Min. 90
	Colour Temperature	2700K
	Lifetime	L90B10 @50,000 Hours
	Lamp Included	Yes
	Number of Light Sources	2
	CIE flux code	91 97 99 50 67
	Binning (SDCM)	2
	Light Direction	Up/Down
	Optic	Collimator
	Measured beam angle (°)	34.0
	Input Voltage	230V
	Luminaire power (W)	11.6
	Electrical Class	1
	IP Rating	20
_	Glow wire rating (°C)	960
	Dimming Protocol	Trailing Edge
	Indoor/Outdoor	Indoor
_	Application	Wall
	Mounting	Surface
_	Adjustability	Not Applicable
	Distance to Lighted Object (m)	0,1
	Primary Colour & Primary Finish	Black, Chrome
	Gross weight (g)	450.0
	Luminous flux per lamp (lm)	693
Ī	Efficacy (Im/W)	60
	Glare rating	24
_		



TM30 & CRI diagram





Light distribution & beam diagram

