

---




---



---




---

*Chival Wall Up/Down 292 2x LED 1800-3000K WD Trailing Edge DI Black Brushed Anodised*


### Specifications

Material	13760281
Light Source Type	LED
LED Type	BRIDGELUX WARM DIM 4W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	88 96 99 50 52
Binning (SDCM)	3
Light Direction	Up/Down
Optic	Collimator
Measured beam angle (°)	43.0
Input Voltage	230V
Luminaire power (W)	10.6
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Wall
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Brushed Anodised
Gross weight (g)	480.0
Luminous flux per lamp (lm)	447
Efficacy (lm/W)	42
Glare rating	24

Formed by one single, pleated plate, Chival shows elements of sharp design and refined craftsmanship. Its up and down vertical light is a natural continuation of the shape, which was inspired by medieval coats of arms. Alone, Chival is beautiful and timeless. Try two or more, and you'll see a conversation of shadow, light and patterns taking shape.

**TM30 & CRI diagram**

**Light distribution & beam diagram**
