

D	ĉ	3	t	e	ł	
0			_	L	_	

Customer

Project

Туре

Spe

Chival Wall Up/Down 292 2x LED 2700K DALI/Push-Dim DI Bronze Brushed Anodised



Formed by one single, pleated plate, Chival shows elements of sharp design and refined craftsmanship. Its up and down vertical light is a natural continuation of the shape, which was inspired by medieval coats of arms. Alone, Chival is beautiful and timeless. Try two or more, and you'll see a conversation of shadow, light and patterns taking shape.


292 54	Frends of hue hue
rial	13760382
Source Type	LED
Туре	CREE 1304
technology	LED COB
	Min. 90
ır Tomporaturo	2700K

Material	13760382
Light Source Type	LED
LED Type	CREE 1304
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	91 97 99 50 66
Binning (SDCM)	2
Light Direction	Up/Down
Optic	Collimator
Measured beam angle (°)	34.0
Input Voltage	230V
Luminaire power (W)	11.6
Electrical Class	1
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI, Push-Dim
DALI Standard	DALI-2
Indoor/Outdoor	Indoor
Application	Wall
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Bronze, Brushed Anodised
Gross weight (g)	485.0
Delivered lumens (Im)	684
Efficacy (Im/W)	59
Glare rating	23



TM30 & CRI diagram





Light distribution & beam diagram

