


| |
|----------|
| Date |
| Customer |
| Project |
| Type |

Chival Wall Up/Down 292 2x LED 2700K DE Black Brushed Anodised



Specifications

| | |
|---------------------------------|----------------------------------|
| Material | 13760681 |
| Light Source Type | LED |
| LED Type | CREE 1304 |
| LED technology | LED COB |
| CRI | Min. 90 |
| Colour Temperature | 2700K |
| Lifetime | L90B10 @50,000 Hours |
| Lamp Included | Yes |
| Number of Light Sources | 2 |
| CIE flux code | 92 98 99 50 65 |
| Binning (SDCM) | 2 |
| Light Direction | Up/Down |
| Optic | Collimator |
| Measured beam angle (°) | 34.0 |
| Input Voltage | Constant Current Driver Required |
| Electrical Class | III |
| IP Rating | 20 |
| Glow wire rating (°C) | 960 |
| Indoor/Outdoor | Indoor |
| Application | Wall |
| Mounting | Surface |
| Adjustability | Not Applicable |
| Distance to Lighted Object (m) | 0,1 |
| Primary Colour & Primary Finish | Black, Brushed Anodised |
| Gross weight (g) | 370.0 |
| Drive current (mA) | 350 500 |
| Min. forward voltage (Vf) | 7,5 7,8 |
| Max. forward voltage (Vf) | 9,5 9,8 |
| Connected load (W) | 3,0 4,4 |
| Luminous flux per lamp (lm) | 497 671 |
| Efficacy (lm/W) | 83 76 |
| Glare rating | 22 23 |

Formed by one single, pleated plate, Chival shows elements of sharp design and refined craftsmanship. Its up and down vertical light is a natural continuation of the shape, which was inspired by medieval coats of arms. Alone, Chival is beautiful and timeless. Try two or more, and you'll see a conversation of shadow, light and patterns taking shape.

TM30 & CRI diagram



Light distribution & beam diagram



Diagrams