


Date
Customer
Project
Туре

Minude Track 48V Suspended 45 1x LED 2700K Medium DALI Black Chrome



Minude's yogic flexibility will surprise you about as much as its bare, cylindrical design. Express a refined and minimalistic look & feel on walls, on high or low ceilings. Try more than one Minude on our Pista track or on our redesigned Modupoint LED. Its long string of colours and miniature size will make a big impression.





a			c·			
Ν	ne.	C11	1.0	ati	\boldsymbol{O}	ns
\sim	P^{-}	ויים	•		•	75

Material	11462180			
Light Source Type	LED			
LED Type	BRIDGELUX V6 HD G7			
LED technology	LED COB			
CRI	Min. 90			
Colour Temperature	2700K			
Lifetime	L80B10 @50,000 Hours			
Lamp Included	Yes			
Number of Light Sources	1			
CIE flux code	100 100 100 100 60			
Binning (SDCM)	2			
Light Direction	Down			
Optic	Lens			
Measured beam angle (°)	29.0			
Input Voltage	48Vdc			
Luminaire power (W)	11.0			
Electrical Class	III			
IP Rating	20			
Glow wire rating (°C)	960			
Dimming Protocol	DALI			
DALI Standard	DALI-2			
Indoor/Outdoor	Indoor			
Application	Ceiling			
Mounting	Suspended			
Adjustability	Not Applicable			
Distance to Lighted Object (m)	0,1			
Primary Colour & Primary Finish	Black, Chrome			
Gross weight (g)	458.0			
Luminous flux per lamp (lm)	578			
Efficacy (Im/W)	53			
Glare rating	1			
Remark	 This is not a complete product. Pista track 48V system required. For installations without dimmer, it is recommended to use 1-10 V luminaires. 			





TM30 & CRI diagram





Light distribution & beam diagram

