


|          |
|----------|
| Date     |
| Customer |
| Project  |
| Type     |

*Nude Wall Up/Down 79 2x IP55 LED 2700K Flood Trailing Edge DI Black Structure*



Nude's pure geometrical lines are ideal for highlighting architectural features. A long, thin, wall luminaire with indirect light, it is completely stripped down to the essence of what constitutes a luminaire. Its light source is recessed in the slender cylinder so much so that it is practically invisible. Complement the light effect with white or black, or a row of rich colours.



**Specifications**

|                                 |   |
|---------------------------------|---|
| Material                        | 10923332  |
| Light Source Type               | LED   |
| LED Type                        | BRIDGELUX V8G8                                      |
| LED technology                  | LED COB   |
| CRI                             | Min. 90   |
| Colour Temperature              | 2700K   |
| Lifetime                        | L90B10 @50,000 Hours                                |
| Lamp Included                   | Yes   |
| Number of Light Sources         | 2   |
| CIE flux code                   | 100 100 100 50 61                                   |
| Binning (SDCM)                  | 2   |
| Light Direction                 | Up/Down   |
| Optic                           | Reflector   |
| Measured beam angle (°)         | 36.0  |
| Input Voltage                   | 230V  |
| Luminaire power (W)             | 11.6  |
| Electrical Class                | I   |
| IP Rating                       | 55  |
| Glow wire rating (°C)           | 960   |
| Dimming Protocol                | Trailing Edge                                       |
| Indoor/Outdoor                  | Outdoor   |
| Application                     | Wall  |
| Mounting                        | Surface   |
| Adjustability                   | Not Applicable                                      |
| Distance to Lighted Object (m)  | 0,1   |
| Primary Colour & Primary Finish | Black, Structure                                    |
| Gross weight (g)                | 1768.0  |
| Luminous flux per lamp (lm)     | 787   |
| Efficacy (lm/W)                 | 68  |
| Glare rating                    | 9   |
| Remark                          | • Not suitable for installation ≤5km from the coast |

**TM30 & CRI diagram**



**Light distribution & beam diagram**

