


Date
Customer
Project
Туре

## Modest Recessed 74 1x IP55 LED 3000K Medium DE Black Structure



An easy-to-install and accessible downlight that does not settle for anything less than high quality. Modest is a classic, recessed luminaire with a surprising rainbow of diversity. Enjoy its absolute simplicity and all the new styles it will bring.





Specif	ications
Material	

Material	13780132	
Light Source Type	LED	
LED Type	BRIDGELU	JX V8G8
LED technology	LED COB	
CRI	Min. 90	
Colour Temperature	3000K	
Lifetime	L80B20 @	50,000 Hours
Lamp Included	Yes	
Number of Light Sources	1	
CIE flux code	100 100 10	00 100 84
Binning (SDCM)	2	
Light Direction	Down	
Optic	Collimator	
Measured beam angle (°)	23.0	
Input Voltage	Constant C	Current Driver Required
Electrical Class	III	
IP Rating	55	
Glow wire rating (°C)	960	
Indoor/Outdoor	Indoor	
Application	Ceiling, Wa	all
Mounting	Recessed	
Cut-out size (mm)	ø68	
Mounting depth (mm)	110.0	
Distance to Lighted Object (m)	0,1	
Primary Colour & Primary Finish	Black, Structure	
Gross weight (g)	190.0	
Drive current (mA)	350	500
Min. forward voltage (Vf)	13,2	13,7
Max. forward voltage (Vf)	15,0	15,4
Connected load (W)	5,0	7,2
Delivered lumens (Im)	562	763
Efficacy (Im/W)	112	106
Glare rating	8	9
_ :		

Remark

<sup>•</sup> This product comes in different standard and full customisation options. Click on the buttons above to discover them all or ask for a quote.




Modular L.I. reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly Latest datasheet and documentation available on www.supermodular.com - 2024-11-22, 06:36:14 PM - ©Modular Lighting Instruments




## TM30 & CRI diagram






## Light distribution & beam diagram






## Installation Accessories



**11624030** Installation Housing 140x250x100x210



**12292630** Gypsum Fibreboard 150x150

Choose a required accessory