


Pate
Customer
Project
уре

## Minude Out Recessed 49 23 1x IP54 LED 2700K Medium DE Cast Grey Matt



Minude's yogic flexibility will surprise you about as much as its bare, cylindrical design. Express a refined and minimalistic look & feel on walls, on high or low ceilings. Try more than one Minude on our Pista track or on our redesigned Modupoint LED. Its long string of colours and miniature size will make a big impression.



Specifications

Connected load (W)

Efficacy (Im/W)

Glare rating

(Im)

Luminous flux per lamp

Material



13641004

Material	13041004
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G7
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 66
Binning (SDCM)	2
Light Direction	Down
Optic	Lens
Measured beam angle (°)	29.0
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	54
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Recessed
Cut-out size (mm)	ø44
Mounting depth (mm)	80.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Cast Grey, Matt
Gross weight (g)	197.0
Drive current (mA)	350 500
Min. forward voltage (Vf)	14.8 15.2
Max. forward voltage (Vf)	18.0 18.6

8.5

640

75

0

475

83

0




## TM30 & CRI diagram






## Light distribution & beam diagram







## Installation Accessories



12293730 Plaster Kit 44 1x



**10889530** Installation Housing 123x100x80



12290730 Plaster Kit 100x120-45 1x

Choose a required accessory