


Date
Customer
Project
Type

Nyto Track 48V Adjustable 30 1x LED 2700K Medium 1-10V Black Structure



Very subtle, Nyto allows you to add a personal touch to the space or match an existing shade in the interior. With plenty of lighting, colour and application options, Nyto is ideal for many places and spaces.



Specifications

Material	13820432
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	99 100 100 100 67
Binning (SDCM)	2
Light Direction	Down
Optic	Collimator
Measured beam angle (°)	25.0
Input Voltage	48Vdc
Luminaire power (W)	7.0
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	1-10V
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	H 360° V 0°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	204.0
Luminous flux per lamp (lm)	490
Efficacy (lm/W)	70
Glare rating	14
Remark	<ul style="list-style-type: none"> • This product comes in different standard and full customisation options. Discover them all on the Nyto Track 48V web page or ask for a quote. • This is not a complete product. Pista track 48V system required.

TM30 & CRI diagram



Light distribution & beam diagram

