


ate
ustomer
roject
уре

Nyto Semi-Recessed Adjustable 30 1x LED 3000K Medium DE Black Structure




Very subtle, Nyto allows you to add a personal touch to the space or match an existing shade in the interior. With plenty of lighting, colour and application options, Nyto is ideal for many places and spaces.





specifications	
Material	
Limbt Course Ture	

Material	13824432
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light	1
Sources	
CIE flux code	99 100 100 100 67
Binning (SDCM)	2
Light Direction	Down
Optic	Collimator
Measured beam angle	25.0
(°)	
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Semi-Recessed
Cut-out size (mm)	ø40
Mounting depth (mm)	110.0
Adjustability	H 360° V 0°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour &	Black, Structure
Primary Finish	
Gross weight (g)	191.0
Drive current (mA)	350
Min. forward voltage (Vf)	15,4
Max. forward voltage (Vf)	18,8
Connected load (W)	6,0
Luminous flux per lamp (lm)	500
Efficacy (Im/W)	83
Glare rating	14
Remark	This product comes in different Direct Custom






options. Discover them all on the Modest Recessed web page or ask for a quote.




TM30 & CRI diagram






Light distribution & beam diagram






Installation Accessories



10889530 Installation Housing 123x100x80



12293130 Plaster Kit 100x120-40 1x

Choose a required accessory