


Date
Customer
Project
Гуре

Nyto Track 48V Adjustable 40 2x LED 2700K Medium DALI White Structure



Very subtle, Nyto allows you to add a personal touch to the space or match an existing shade in the interior. With plenty of lighting, colour and application options, Nyto is ideal for many places and spaces.





C-		٠.;	<i>C:</i> -	a. 4.	: .	
SĽ	vec	: 1	ιc	au	ιo	ns

Material	13832909
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	99 100 100 100 79
Binning (SDCM)	2
Light Direction	Down
Optic	Collimator
Measured beam angle (°)	31.0
Input Voltage	48Vdc
Luminaire power (W)	19.0
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI
DALI Standard	DALI-2
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	H 360° V 0°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	504.0
Luminous flux per lamp (lm)	780
Efficacy (Im/W)	82
Glare rating	14
Demark	• This Track 18\/ luminaire can not be used in the

Remark

• This Track 48V luminaire can not be used in the upper part of a Pista Track 48V Profile Suspended Up/Down.

 White Pista 48V luminaires have a white track adapter. All other Pista 48V luminaires have a black track adapter. Deviation from this is only





possible on request.

- This product comes in different standard and full customisation options. Discover them all on the Nyto Track 48V web page or ask for a quote.
- This is not a complete product. Pista track 48V system required.




TM30 & CRI diagram







Optical Accessories



10223032 Honeycomb 28 Black

Choose a required accessory