


Date
Customer
Project
Type

*Nyto Track 48V Adjustable 50 lx LED 2700K Medium 1-10V White Structure*



Very subtle, Nyto allows you to add a personal touch to the space or match an existing shade in the interior. With plenty of lighting, colour and application options, Nyto is ideal for many places and spaces.



**Specifications**

Material	13840709
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	99 100 100 100 84
Binning (SDCM)	2
Light Direction	Down
Optic	Collimator
Measured beam angle (°)	28.0
Input Voltage	48Vdc
Luminaire power (W)	14.9
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	1-10V
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	H 360° V 0°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	309.0
Luminous flux per lamp (lm)	1079
Efficacy (lm/W)	72
Glare rating	13
Remark	<ul style="list-style-type: none"> <li>• This product comes in different standard and full customisation options. Discover them all on the Nyto Track 48V web page or ask for a quote.</li> <li>• This is not a complete product. Pista track 48V system required.</li> </ul>

**TM30 & CRI diagram**



**Light distribution & beam diagram**

