


Pate
Customer
Project
уре

Nyto Track 48V Adjustable 50 2x LED 3000K Medium DALI White Structure



Very subtle, Nyto allows you to add a personal touch to the space or match an existing shade in the interior. With plenty of lighting, colour and application options, Nyto is ideal for many places and spaces.






13844709

a		٠,	c·			
7	ne.	C11	1C	at	10	ns
\sim	ρ \boldsymbol{c}	~,,	"	CV V	, ,	

Material

Material	13044709
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	99 100 100 100 91
Binning (SDCM)	2
Light Direction	Down
Optic	Collimator
Measured beam angle (°)	28.0
Input Voltage	48Vdc
Luminaire power (W)	36.7
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI
DALI Standard	DALI-2
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	H 360° V 0°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	554.0
Luminous flux per lamp (lm)	1302
Efficacy (Im/W)	71
Glare rating	14
Remark	This Track 48V luminaire can not be used in the

- This Track 48V luminaire can not be used in the upper part of a Pista Track 48V Profile Suspended Up/Down.
- White Pista 48V luminaires have a white track adapter. All other Pista 48V luminaires have a black track adapter. Deviation from this is only





possible on request.

- This product comes in different standard and full customisation options. Discover them all on the Nyto Track 48V web page or ask for a quote.
- This is not a complete product. Pista track 48V system required.



TM30 & CRI diagram



