


Date
Customer
Project
Type

Passage Semi-Recessed Adjustable 40 lx LED 2700K Medium DE White Matt



The name Passage refers to continuity, both within the object and beyond it. The flat hinge creates a passage in the composition, while the product itself becomes a passage of light, a passage of time, a connection held in form.




Specifications

Material	13960138		
Light Source Type	LED		
LED Type	CITIZEN CLU7A3		
LED technology	LED COB		
CRI	Min. 90		
Colour Temperature	2700K		
Lifetime	L90B10 @50,000 Hours		
Lamp Included	Yes		
Number of Light Sources	1		
CIE flux code	99 100 100 100 70		
Binning (SDCM)	2		
Light Direction	Down		
Optic	Collimator		
Measured beam angle (°)	27.0		
Input Voltage	Constant Current Driver Required		
Electrical Class	III		
IP Rating	20		
Glow wire rating (°C)	960		
Indoor/Outdoor	Indoor		
Application	Ceiling, Wall		
Mounting	Semi-Recessed		
Cut-out size (mm)	Ø54		
Mounting depth (mm)	45.0		
Adjustability	H 360° V 0°/+90°		
Distance to Lighted Object (m)	0,1		
Primary Colour & Primary Finish	White, Matt		
Gross weight (g)	505.0		
Drive current (mA)	350	500	700
Min. forward voltage (Vf)	11.2	11.2	11.2
Max. forward voltage (Vf)	13.2	13.2	13.2
Connected load (W)	4.1	6.1	9.0
Luminous flux per lamp (lm)	344	465	598
Efficacy (lm/W)	84	76	66
Glare rating	10	11	12



Remark	• 3500K and 4000K on request
--------	------------------------------

TM30 & CRI diagram



Light distribution & beam diagram

