

Date

Customer


Project

Type

## Passage Semi-Recessed Adjustable 40 lx LED 2700K Flood DE White Matt



The name Passage refers to continuity, both within the object and beyond it. The flat hinge creates a passage in the composition, while the product itself becomes a passage of light, a passage of time, a connection held in form.




### Specifications

|                                 |                                  |      |      |
|---------------------------------|----------------------------------|------|------|
| Material                        | 13960238                         |      |      |
| Light Source Type               | LED                              |      |      |
| LED Type                        | CITIZEN CLU7A3                   |      |      |
| LED technology                  | LED COB                          |      |      |
| CRI                             | Min. 90                          |      |      |
| Colour Temperature              | 2700K                            |      |      |
| Lifetime                        | L90B10 @50,000 Hours             |      |      |
| Lamp Included                   | Yes                              |      |      |
| Number of Light Sources         | 1                                |      |      |
| CIE flux code                   | 99 100 100 100 70                |      |      |
| Binning (SDCM)                  | 2                                |      |      |
| Light Direction                 | Down                             |      |      |
| Optic                           | Collimator                       |      |      |
| Measured beam angle (°)         | 42.0                             |      |      |
| Input Voltage                   | Constant Current Driver Required |      |      |
| Electrical Class                | III                              |      |      |
| IP Rating                       | 20                               |      |      |
| Glow wire rating (°C)           | 960                              |      |      |
| Indoor/Outdoor                  | Indoor                           |      |      |
| Application                     | Ceiling, Wall                    |      |      |
| Mounting                        | Semi-Recessed                    |      |      |
| Cut-out size (mm)               | ø54                              |      |      |
| Mounting depth (mm)             | 45.0                             |      |      |
| Adjustability                   | H 360° V 0°/+90°                 |      |      |
| Distance to Lighted Object (m)  | 0,1                              |      |      |
| Primary Colour & Primary Finish | White, Matt                      |      |      |
| Gross weight (g)                | 505.0                            |      |      |
| Drive current (mA)              | 350                              | 500  | 700  |
| Min. forward voltage (Vf)       | 11,2                             | 11,2 | 11,2 |
| Max. forward voltage (Vf)       | 13,2                             | 13,2 | 13,2 |
| Connected load (W)              | 4,1                              | 6,1  | 9,0  |
| Luminous flux per lamp (lm)     | 347                              | 468  | 602  |
| Efficacy (lm/W)                 | 85                               | 77   | 67   |
| Glare rating                    | 16                               | 17   | 18   |




|        |                              |
|--------|------------------------------|
| Remark | • 3500K and 4000K on request |
|--------|------------------------------|

TM30 &amp; CRI diagram



Light distribution &amp; beam diagram



Diagrams