


Date
Customer
Project
Type

Kup Recessed 72 lx IP55 LED 2700K Flood DE Bronze Brushed Anodised



Kup is a refined round recessed spotlight that brings character to the ceiling through its distinctive raised edge and expressive cup-shaped design. Behind its pure Ø72 form lies an extensive optical platform, offering the flexibility to highlight both objects and spaces with precision. Extensive finish and colour personalisation options allow Kup to adapt effortlessly to any interior




Specifications


Material	14281282		
Light Source Type	LED		
LED Type	CREE CHA0410		
LED technology	LED COB		
CRI	Min. 90		
Colour Temperature	2700K		
Lifetime	L90B05 @50,000 Hours		
Lamp Included	Yes		
Number of Light Sources	1		
CIE flux code	99 100 100 100 82		
Binning (SDCM)	2		
Light Direction	Down		
Optic	Collimator		
Measured beam angle (°)	41.0		
Input Voltage	Constant Current Driver Required		
Electrical Class	III		
IP Rating	55		
Glow wire rating (°C)	960		
Indoor/Outdoor	Indoor		
Application	Ceiling		
Mounting	Recessed		
Cut-out size (mm)	ø68		
Mounting depth (mm)	100.0		
Adjustability	Not Applicable		
Distance to Lighted Object (m)	0,1		
Primary Colour & Primary Finish	Bronze, Brushed Anodised		
Gross weight (g)	314.0		
Drive current (mA)	350	500	700
Min. forward voltage (Vf)	10,4	10,8	11,4
Max. forward voltage (Vf)	12,7	13,2	13,7
Connected load (W)	4,1	6,1	8,8
Luminous flux per lamp (lm)	377	514	675
Efficacy (lm/W)	92	84	77
Glare rating	17	18	19




Remark	• 2400K on request • CRI98 on request • This product comes in different Direct Custom options. Discover them all on the Kup Recessed web page or ask for a quote.
--------	---



Installation Accessories



12292630 Gypsum Fibreboard 150x150



11624030 Installation Housing 140x250x100x210

Choose a required accessory