


Date
Customer
Project
Type

Nyto Surface Adjustable 60 Round 1x LED 2700K Medium DE Black Structure - Black Structure



Very subtle, Nyto allows you to add a personal touch to the space or match an existing shade in the interior. With plenty of lighting, colour and application options, Nyto is ideal for many places and spaces.




Specifications


Material	13994232
Light Source Type	LED
LED Type	FORTIMO SLM 1204 GEN8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	98 100 100 100 83
Binning (SDCM)	2
Light Direction	Down
Optic	Collimator
Measured beam angle (°)	28.0
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Surface
Adjustability	H 360° V 0°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Secondary Colour & Secondary Finish	Black, Structure
Gross weight (g)	438.0
Drive current (mA)	350 500
Min. forward voltage (Vf)	33,6 34,9
Max. forward voltage (Vf)	35,7 37,0
Connected load (W)	12,0 17,8
Luminous flux per lamp (lm)	1560 2137
Efficacy (lm/W)	130 120
Glare rating	14 16

Remark	• This product comes in different Direct Custom options. Discover them all on the Nyto Surface web page or ask for a quote.
--------	---


TM30 & CRI diagram



Light distribution & beam diagram



Optical Accessories



10217702 Honeycomb 44 Black Matt

Choose a required accessory