

| Date |
|----------|
| Customer |
| Project |
| Туре |

Lotis Tube Wall Up/Down 85 2x GU10 White Structure - Gold Anodised



Lotis Tubed is an extremely fun and versatile cylinder. You get to choose the colour of the spotlight and match it with a white or black cylinder. Go for a contrast between black, white and gold or choose a more uniform look instead. Surface-mounted, wall-mounted or suspended versions are available.

| 80] 275 e 85 Specifications | Frends of hue |
|---|--|
| Material | 10883789 |
| Light Source Type | GU10 |
| Lifetime | L80B20 @50,000 Hours |
| Lamp Included | No |
| Number of Light Sources | 2 |
| Light Direction | Up/Down |
| Optic | Reflector |
| | |
| Input Voltage | 230V |
| Input Voltage Electrical Class | 230V I |
| | |
| Electrical Class | |
| Electrical Class IP Rating | l 20 |
| Electrical Class IP Rating Glow wire rating (°C) | l 20 960 |
| Electrical Class IP Rating Glow wire rating (°C) Indoor/Outdoor | l 20 960 Indoor |
| Electrical Class IP Rating Glow wire rating (°C) Indoor/Outdoor Application | l 20 960 Indoor Wall |
| Electrical Class IP Rating Glow wire rating (°C) Indoor/Outdoor Application Mounting | l 20 960 Indoor Wall Surface |
| Electrical Class IP Rating Glow wire rating (°C) Indoor/Outdoor Application Mounting Adjustability Distance to Lighted | l 20 960 Indoor Wall Surface Not Applicable |
| Electrical Class IP Rating Glow wire rating (°C) Indoor/Outdoor Application Mounting Adjustability Distance to Lighted Object (m) Primary Colour & | I 20 960 Indoor Wall Surface Not Applicable 0,5 |
| Electrical Class IP Rating Glow wire rating (°C) Indoor/Outdoor Application Mounting Adjustability Distance to Lighted Object (m) Primary Colour & Primary Finish Secondary Colour & | I 20 960 Indoor Wall Surface Not Applicable 0,5 White, Structure |



Light distribution & beam diagram

