


Date
Customer
Project
Type

FFD_Nude Wall Up/Down 70 2x LED PAR20 E27 2700K Medium Leading Edge Champagne Brushed Anodised



Specifications

Material	10922241
Light Source Type	LED PAR20 E27
LED Type	PHILIPS MASTERLED PAR20 6W
LED technology	LED high power
CRI	Min. 80
Colour Temperature	2700K
Lifetime	L70B50 @25,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	97 100 100 100 99
Binning (SDCM)	3
Light Direction	Up/Down
Optic	Collimator
Measured beam angle (°)	21.2
Input Voltage	230V
Luminaire power (W)	12.0
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Leading Edge
Indoor/Outdoor	Indoor
Application	Wall
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Champagne, Brushed Anodised
Gross weight (g)	1266.0
Luminous flux per lamp (lm)	1039
Efficacy (lm/W)	86
Glare rating	7

Nude's pure geometrical lines are ideal for highlighting architectural features. A long, thin, wall luminaire with indirect light, it is completely stripped down to the essence of what constitutes a luminaire. Its light source is recessed in the slender cylinder so much so that it is practically invisible. Complement the light effect with white or black, or a row of rich colours.

Light distribution & beam diagram

