

FFD_Nude Wall Up/Down 70 2x LED PAR20 E27 2700K Medium Leading Edge Bronze Brushed Anodised



Specifications

| | |
|---------------------------------|----------------------------|
| Material | 10922282 |
| Light Source Type | LED PAR20 E27 |
| LED Type | PHILIPS MASTERLED PAR20 6W |
| LED technology | LED high power |
| CRI | Min. 80 |
| Colour Temperature | 2700K |
| Lifetime | L70B50 @25,000 Hours |
| Lamp Included | Yes |
| Number of Light Sources | 2 |
| CIE flux code | 97 100 100 100 99 |
| Binning (SDCM) | 3 |
| Light Direction | Up/Down |
| Optic | Collimator |
| Measured beam angle (°) | 22.3 |
| Input Voltage | 230V |
| Luminaire power (W) | 12.0 |
| Electrical Class | I |
| IP Rating | 20 |
| Glow wire rating (°C) | 960 |
| Dimming Protocol | Leading Edge |
| Indoor/Outdoor | Indoor |
| Application | Wall |
| Mounting | Surface |
| Adjustability | Not Applicable |
| Distance to Lighted Object (m) | 0,1 |
| Primary Colour & Primary Finish | Bronze, Brushed Anodised |
| Gross weight (g) | 1266.0 |
| Luminous flux per lamp (lm) | 1031 |
| Efficacy (lm/W) | 85 |
| Glare rating | 6 |

Nude's pure geometrical lines are ideal for highlighting architectural features. A long, thin, wall luminaire with indirect light, it is completely stripped down to the essence of what constitutes a luminaire. Its light source is recessed in the slender cylinder so much so that it is practically invisible. Complement the light effect with white or black, or a row of rich colours.

Light distribution & beam diagram
