


| Date     |  |
|----------|--|
| Customer |  |
| Project  |  |
| Туре     |  |

## FFD\_Nude Wall 79 1x IP55 LED 3000K Flood DI Aluminium Structure



Nude's pure geometrical lines are ideal for highlighting architectural features. A long, thin, wall luminaire with indirect light, it is completely stripped down to the essence of what constitutes a luminaire. Its light source is recessed in the slender cylinder so much so that it is practically invisible. Complement the light effect with white or black, or a row of rich colours.





| Specifications                    |   |
|-----------------------------------|---|
| Material                          | 10923024  |
| Light Source Type                 | LED   |
| LED Type                          | BRIDGELUX V8G6                                      |
| LED technology                    | LED COB   |
| CRI                               | Min. 90   |
| Colour Temperature                | 3000K   |
| Lifetime                          | L80B20 @50,000 Hours                                |
| Lamp Included                     | Yes   |
| Number of Light<br>Sources        | 1   |
| CIE flux code                     | 99 99 100 100 56                                    |
| Binning (SDCM)                    | 3   |
| Light Direction                   | Up, Down  |
| Optic                             | Reflector   |
| Measured beam angle (°)           | 38.7  |
| Input Voltage                     | 230V  |
| Luminaire power (W)               | 8.0   |
| Electrical Class                  | 1   |
| IP Rating                         | 55  |
| Glow wire rating (°C)             | 960   |
| Indoor/Outdoor                    | Outdoor   |
| Application                       | Wall  |
| Mounting                          | Surface   |
| Adjustability                     | Not Applicable                                      |
| Distance to Lighted<br>Object (m) | 0,1   |
| Primary Colour & Primary Finish   | Aluminium, Structure                                |
| Gross weight (g)                  | 1491.0  |
| Luminous flux per lamp (lm)       | 321   |
| Efficacy (Im/W)                   | 40  |
| Glare rating                      | 9   |
| Remark                            | • Not suitable for installation ≤5km from the coast |



## TM30 & CRI diagram



