


Date
Customer
Project
Туре

Duell Wall Up/Down 2x LED 2700K DALI DI White Structure - Champagne Anodised



Duell's gentle curves are sure to give any space a softer touch. This two-colour, LED luminaire invites you to play with combinations. One for the outside, and one for the inside plate. For ceiling-mounted applications, recessed and surface-mounted variants are available. The recessed version has an attractive broad rim, while the surface version also offers a directional variant.





Specifications	
Material	11074809
Light Source Type	LED
LED Type	BRIDGELUX V8G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	68 93 99 50 59
Binning (SDCM)	2
Light Direction	Up/Down
Optic	Lens
Input Voltage	230V
Luminaire power (W)	12.0
Electrical Class	
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI
DALI Standard	DALI-2
Indoor/Outdoor	Indoor
Application	Wall
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Secondary Colour & Secondary Finish	Champagne, Anodised
Gross weight (g)	1181.0
Luminous flux per lamp (lm)	763
Efficacy (Im/W)	64
Glare rating	17



TM30 & CRI diagram





Light distribution & beam diagram

