





| Pate     |
|----------|
| Customer |
| Project  |
| уре      |

Duell Wall Up/Down 2x IP55 LED 2700K Non-Dim DI White Structure - Champagne Anodised



Duell's gentle curves are sure to give any space a softer touch. This two-colour, LED luminaire invites you to play with combinations. One for the outside, and one for the inside plate. For ceiling-mounted applications, recessed and surface-mounted variants are available. The recessed version has an attractive broad rim, while the surface version also offers a directional variant.





| specifications |  |
|----------------|--|
| Vlaterial      |  |

| Material                            | 11075039  |
|-------------------------------------|---|
| Light Source Type                   | LED   |
| LED Type                            | OPTOGA 230VAC                                       |
| LED technology                      | LED PCB   |
| CRI                                 | Min. 90   |
| Colour Temperature                  | 2700K   |
| Lifetime                            | L80B20 @50,000 Hours                                |
| Lamp Included                       | Yes   |
| Number of Light<br>Sources          | 2   |
| CIE flux code                       | 64 90 98 50 72                                      |
| Binning (SDCM)                      | 3   |
| Light Direction                     | Up/Down   |
| Input Voltage                       | 230V  |
| Luminaire power (W)                 | 12.0  |
| Electrical Class                    | 1   |
| IP Rating                           | 55  |
| Glow wire rating (°C)               | 960   |
| Dimming Protocol                    | Non-Dim   |
| Indoor/Outdoor                      | Outdoor   |
| Application                         | Wall  |
| Mounting                            | Surface   |
| Adjustability                       | Not Applicable                                      |
| Distance to Lighted Object (m)      | 0,1   |
| Primary Colour & Primary Finish     | White, Structure                                    |
| Secondary Colour & Secondary Finish | Champagne, Anodised                                 |
| Gross weight (g)                    | 1144.0  |
| Luminous flux per lamp (lm)         | 651   |
| Efficacy (Im/W)                     | 54  |
| Glare rating                        | 18  |
| Remark                              | • Not suitable for installation ≤5km from the coast |



| TM30 & CRI diagram | Light distribution & beam diagram |  |
|--------------------|-----------------------------------|--|
|                    |                                   |  |
|                    |                                   |  |
|                    |                                   |  |
|                    |                                   |  |
|                    |                                   |  |
|                    |                                   |  |
|                    |                                   |  |
|                    |                                   |  |
|                    |                                   |  |
|                    |                                   |  |
|                    |                                   |  |
|                    |                                   |  |