


Datum	
Kunde	
Projekt	
Art	

## M-LED Module 111 1x LED 2700K Medium DE White Structure







11298109		
LED		
BRIDGELUX VERO13		
COB-LED		
Min. 90		
2700K		
L80 B20 bei 50.000 Stunden		
Ja		
1		
3		
Reflektor		
Konstantstrom-Treiber erforderlich		
III		
20		
960		
Innen		
Not Applicable		
0,1		
Weiß, Stru	ukturiert	
474,0		
350	500	700
29,1	29,9	31,0
33,7	34,7	35,8
11,0	16,2	23,4
920	1256	1625
84	77	69
16	17	18
	LED BRIDGELI COB-LED Min. 90 2700K L80 B20 b Ja 1 3 Reflektor Konstants III 20 960 Innen Not Applic 0,1 Weiß, Stru 474,0 350 29,1 33,7 11,0 920 84	BRIDGELUX VERO COB-LED Min. 90 2700K L80 B20 bei 50.000 Ja 1 3 Reflektor Konstantstrom-Trei III 20 960 Innen Not Applicable 0,1 Weiß, Strukturiert  474,0 350 500 29,1 29,9 33,7 34,7 11,0 16,2 920 1256



## TM30 & CRI Diagramm





## Lichtverteilung und Lichtverteilungskurve

