

Date
Customer
Project
Type

M-LED Module 111 1x LED 4000K Flood DE Aluminium Brushed Anodised




Specifications

Material	11298824		
Light Source Type	LED		
LED Type	BRIDGELUX VERO13		
LED technology	LED COB		
CRI	Min. 90		
Colour Temperature	4000K		
Lifetime	L80B20 @50,000 Hours		
Lamp Included	Yes		
Number of Light Sources	1		
Binning (SDCM)	3		
Optic	Reflector		
Input Voltage	Constant Current Driver Required		
Electrical Class	III		
IP Rating	20		
Glow wire rating (°C)	960		
Indoor/Outdoor	Indoor		
Adjustability	Not Applicable		
Distance to Lighted Object (m)	0,1		
Primary Colour & Primary Finish	Aluminium, Brushed Anodised		
Gross weight (g)	474.0		
Drive current (mA)	350	500	700
Min. forward voltage (Vf)	29,1	29,9	31,0
Max. forward voltage (Vf)	33,7	34,7	35,8
Connected load (W)	11,0	16,2	23,4
Luminous flux per lamp (lm)	1057	1418	1584
Efficacy (lm/W)	96	87	67
Glare rating	18	19	19

TM30 & CRI diagram



Light distribution & beam diagram



Diagrams