


Date
Customer
Project
Type

*Minude Track 48V Suspended 45 1x LED 3000K Medium DALI Silver Bronze Brushed Anodised*



Minude's yogic flexibility will surprise you about as much as its bare, cylindrical design. Express a refined and minimalistic look & feel on walls, on high or low ceilings. Try more than one Minude, on our Pista track or on our redesigned Modupoint LED. Its long string of colours and miniature size will make a big impression.



### Specifications

Material	11462384
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G7
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 71
Binning (SDCM)	2
Light Direction	Down
Optic	Lens
Measured beam angle (°)	29.3
Input Voltage	48Vdc
Luminaire power (W)	11.0
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI
DALI Standard	DALI-2
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Suspended
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Silver Bronze, Brushed Anodised
Gross weight (g)	458.0
Luminous flux per lamp (lm)	612
Efficacy (lm/W)	56
Glare rating	2
Remark	<ul style="list-style-type: none"> <li>• This is not a complete product. Pista track 48V system required.</li> <li>• For installations without dimmer, it is recommended to use 1-10 V luminaires.</li> </ul>



**TM30 & CRI diagram**



**Light distribution & beam diagram**

