




Date
Customer
Project
Type



*Minude Suspended 45 1x LED 2700K Medium DE Silver Bronze Brushed Anodised*




### Specifications

Material	11465084
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G7
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 62
Binning (SDCM)	2
Light Direction	Down
Optic	Lens
Measured beam angle (°)	29.3
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Suspended
Cut-out size (mm)	Ø44
Mounting depth (mm)	70.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Silver Bronze, Brushed Anodised
Gross weight (g)	373.0
Drive current (mA)	350 500
Min. forward voltage (Vf)	14,8 15,2
Max. forward voltage (Vf)	18,0 18,6
Connected load (W)	5,7 8,5
Luminous flux per lamp (lm)	444 599
Efficacy (lm/W)	78 71
Glare rating	1 2


Minude's yogic flexibility will surprise you about as much as its bare, cylindrical design. Express a refined and minimalistic look & feel on walls, on high or low ceilings. Try more than one Minude on our Pista track or on our redesigned Modupoint LED. Its long string of colours and miniature size will make a big impression.

**TM30 & CRI diagram**

**Light distribution & beam diagram**



### *Installation Accessories*



**10889530** Installation Housing 123x100x80



**12290730** Plaster Kit 100x120-45 1x



**12293730** Plaster Kit 44 1x

Choose a required accessory