

Date
Customer
Project
Type


Qbini General 2x IP55 LED 2700K DE White Structure



Specifications

Material	11480009
Light Source Type	LED
LED Type	SAMSUNG LM301B - Qbini General 2x
LED technology	LED PCB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	60 90 99 100 68
Binning (SDCM)	3
Light Direction	Down
Measured beam angle (°)	84.4
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	55
Glow wire rating (°C)	650
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	360.0
Drive current (mA)	350 500
Min. forward voltage (Vf)	11,9 11,9
Max. forward voltage (Vf)	12,2 12,2
Connected load (W)	4,2 6,0
Luminous flux per lamp (lm)	402 560
Efficacy (lm/W)	96 93
Glare rating	29 31
Remark	<ul style="list-style-type: none"> • Qbini Frame and Qbini Box not included • This is not a complete product. Qbini Frame or Qbini Box system required. • This is not a complete product. Qbini Frame or Qbini Box system required.

TM30 & CRI diagram



Light distribution & beam diagram

