


Date
Customer
Project
Type

Medard Recessed 70 lx IP55 LED 2700K Flood DE Black Structure





The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.



Specifications

Material	11551132
Light Source Type	LED
LED Type	BRIDGELUX V8G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 78
Binning (SDCM)	2
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	35.1
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	55
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Recessed
Cut-out size (mm)	ø65
Mounting depth (mm)	95.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	255.0
Drive current (mA)	350 500 700
Min. forward voltage (Vf)	13,2 13,7 14,2
Max. forward voltage (Vf)	15,0 15,4 16,0
Connected load (W)	5,0 7,2 10,6
Delivered lumens (lm)	433 582 747
Efficacy (lm/W)	87 81 70
Glare rating	16 17 18
Remark	• 4000K on request

TM30 & CRI diagram



Light distribution & beam diagram

