


Date
Customer
Project
Type

## Medard Recessed 70 lx IP55 LED 3000K Flood DE White Structure



The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.



### Specifications

Material	11551309		
Light Source Type	LED		
LED Type	BRIDGELUX V8G8		
LED technology	LED COB		
CRI	Min. 90		
Colour Temperature	3000K		
Lifetime	L80B20 @50,000 Hours		
Lamp Included	Yes		
Number of Light Sources	1		
CIE flux code	100 100 100 100 78		
Binning (SDCM)	2		
Light Direction	Down		
Optic	Reflector		
Measured beam angle (°)	35.0		
Input Voltage	Constant Current Driver Required		
Electrical Class	III		
IP Rating	55		
Glow wire rating (°C)	960		
Indoor/Outdoor	Indoor		
Application	Ceiling, Wall		
Mounting	Recessed		
Cut-out size (mm)	ø65		
Mounting depth (mm)	95.0		
Adjustability	Not Applicable		
Distance to Lighted Object (m)	0,1		
Primary Colour & Primary Finish	White, Structure		
Gross weight (g)	255.0		
Drive current (mA)	350	500	700
Min. forward voltage (Vf)	13,2	13,7	14,2
Max. forward voltage (Vf)	15,0	15,4	16,0
Connected load (W)	5,0	7,2	10,6
Delivered lumens (lm)	450	604	777
Efficacy (lm/W)	90	84	73
Glare rating	16	18	18
Remark	• 4000K on request		



### TM30 & CRI diagram



### Light distribution & beam diagram

