



Thimble Recessed 74 1x IP55 LED 2700K Medium DE Champagne Brushed Anodised

Specifications

Material	11620041	
Light Source Type	LED	
LED Type	BRIDGELUX V6 HD G7	
LED technology	LED COB	
CRI	Min. 90	
Colour Temperature	2700K	
Lifetime	L80B10 @50,000 Hours	
Lamp Included	Yes	
Number of Light Sources	1	
CIE flux code	100 100 100 100 61	
Binning (SDCM)	2	
Light Direction	Down	
Optic	Lens	
Measured beam angle (°)	30.0	
Input Voltage	Constant Current Driver Required	
Electrical Class	III	
IP Rating	55	
Glow wire rating (°C)	960	
Indoor/Outdoor	Indoor	
Application	Ceiling	
Mounting	Recessed	
Cut-out size (mm)	Ø70	
Mounting depth (mm)	110.0	
Adjustability	Not Applicable	
Distance to Lighted Object (m)	0,1	
Primary Colour & Primary Finish	Champagne, Brushed Anodised	
Gross weight (g)	254.0	
Drive current (mA)	350	500
Min. forward voltage (Vf)	14,8	15,2
Max. forward voltage (Vf)	18,0	18,6
Connected load (W)	5,7	8,5
Luminous flux per lamp (lm)	440	593
Efficacy (lm/W)	77	70
Glare rating	0	0
Remark	• 4000K on request	






TM30 & CRI diagram




Light distribution & beam diagram



Sample	CRI	R9
R1	91	90.9
R2	92	64.5
R3	91	
R4	92	
R5	89	
R6	89	
R7	94	
R8	85	
R9	64	
R10	81	
R11	91	
R12	73	
R13	91	
R14	94	
R15	89	

Installation Accessories

11624030 Installation Housing 140x250x100x210

12292630 Gypsum Fibreboard 150x150

11624430 Concrete Ring 70 Standard Installation Housing

11624330 Ring Recessed 70 1x

12292430 Plaster Kit Trimless 150x150 - 70 1x



11624230 Concrete Kit 70 150x150 1x

Choose a required accessory