


Date
Customer
Project
Туре

Thimble Recessed Trimless Adjustable 70 1x LED 2700K Medium DE Gold Brushed Anodised



Minimalistic design, subtle curves, revealing colours, high-quality lens and LED. With its deep-recessed and glare-free light source, Thimble's clean and seamless execution makes it a quiet yet sophisticated choice for high-end residential or hospitality settings. This versatile, elegant architectural downlighter brings pure form, definition and quality light without stealing all the attention.



Specifications	
Material	11623042
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G7
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 61
Binning (SDCM)	2
Light Direction	Down
Optic	Lens
Measured beam angle (°)	30.0
Input Voltage	Constant Current Driver Required
Electrical Class	
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Recessed
Cut-out size (mm)	ø86 for plastered concrete ceilings, ø105 for false ceilings
Mounting depth (mm)	110.0
Adjustability	H 360° V 30°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Gold, Brushed Anodised
Gross weight (g)	199.0
Drive current (mA)	350 500
Min. forward voltage (Vf)	14,8 15,2
Max. forward voltage (Vf)	18,0 18,6
Connected load (W)	5,7 8,5
Delivered lumens (Im)	437 590
Efficacy (Im/W)	77 69
Glare rating	0 0
Remark	• 4000K on request






TM30 & CRI diagram






Light distribution & beam diagram






Installation Accessories




11624230 Concrete Kit 70 150x150 1x




11624430 Concrete Ring 70 Standard Installation Housing



11624030 Installation Housing 140x250x100x210




12292630 Gypsum Fibreboard 150x150



12293630 Plaster Kit Trimless 150x150 - 70 1x





11624730 Ring Recessed Trimless 70 1x

Choose a required accessory