










Date
Customer
Project
Type


*Thimble Recessed Trimless Adjustable 70 1x LED 2700K Medium DE Black Brushed Anodised*

**Specifications**

Material	11623081	
Light Source Type	LED	
LED Type	BRIDGELUX V6 HD G7	
LED technology	LED COB	
CRI	Min. 90	
Colour Temperature	2700K	
Lifetime	L80B10 @50,000 Hours	
Lamp Included	Yes	
Number of Light Sources	1	
CIE flux code	100 100 100 100 62	
Binning (SDCM)	2	
Light Direction	Down	
Optic	Lens	
Measured beam angle (°)	30.0	
Input Voltage	Constant Current Driver Required	
Electrical Class	III	
IP Rating	20	
Glow wire rating (°C)	960	
Indoor/Outdoor	Indoor	
Application	Ceiling	
Mounting	Recessed	
Cut-out size (mm)	Ø111	
Mounting depth (mm)	110.0	
Adjustability	H 360° V 30°	
Distance to Lighted Object (m)	0,1	
Primary Colour & Primary Finish	Black, Brushed Anodised	
Gross weight (g)	199.0	
Drive current (mA)	350	500
Min. forward voltage (Vf)	14,8	15,2
Max. forward voltage (Vf)	18,0	18,6
Connected load (W)	5,7	8,5
Luminous flux per lamp (lm)	438	591
Efficacy (lm/W)	77	70
Glare rating	0	0
Remark	• 4000K on request	



**TM30 & CRI diagram**

**Light distribution & beam diagram**


**Installation Accessories**

**11624230** Concrete Kit 70 150x150 1x

**11624430** Concrete Ring 70 Standard Installation Housing

**11624030** Installation Housing 140x250x100x210

**12292630** Gypsum Fibreboard 150x150

**12293630** Plaster Kit Trimless 150x150 - 70 1x



**11624730** Ring Recessed Trimless 70 1x

Choose a required accessory