


Date
Customer
Project
Type

FFD_Medard Stretched Semi-Recessed Adjustable 70 1x LED 2700K Medium DE Black Structure




The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.



Specifications

Material	11652032
Light Source Type	LED
LED Type	BRIDGELUX VERO13
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 88
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	25.0
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Semi-Recessed
Cut-out size (mm)	Ø54
Mounting depth (mm)	40.0
Adjustability	H 360° V 360°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	1334.0
Drive current (mA)	350 500
Min. forward voltage (Vf)	29,1 29,9
Max. forward voltage (Vf)	33,7 34,7
Connected load (W)	11,0 16,2
Delivered lumens (lm)	936 1285
Efficacy (lm/W)	85 79
Glare rating	16 17

TM30 & CRI diagram



Light distribution & beam diagram

