


Date
Customer
Project
Type

FFD_Nomad Surface Adjustable 4x LED 2700K Flood DE White Structure




Like industrial design with a retro touch? Revisit Nomad. Now sporting tiny new drivers, and a LED unit that looks exactly like the luminaire's first halogen bulb, Nomad LED respects the original design to perfection. Available in versions with 2L and 4L light units, in white structure, black or aluminium, with or without integrated gear. The sweetheart of architects is back for your next project.




Specifications

Material	12024209		
Light Source Type	LED		
LED Type	BRIDGELUX VERO13		
LED technology	LED COB		
CRI	Min. 90		
Colour Temperature	2700K		
Lifetime	L80B20 @50,000 Hours		
Lamp Included	Yes		
Number of Light Sources	4		
Binning (SDCM)	3		
Light Direction	Down		
Optic	Reflector		
Measured beam angle (°)	41.3		
Input Voltage	Constant Current Driver Required		
Electrical Class	III		
IP Rating	20		
Glow wire rating (°C)	960		
Indoor/Outdoor	Indoor		
Application	Ceiling, Wall		
Mounting	Surface		
Adjustability	GIMBLE 45°		
Distance to Lighted Object (m)	0,1		
Primary Colour & Primary Finish	White, Structure		
Gross weight (g)	3100.0		
Drive current (mA)	350	500	700
Min. forward voltage (Vf)	29,1	29,9	31,0
Max. forward voltage (Vf)	33,7	34,7	35,8
Connected load (W)	11,0	16,2	23,4
Luminous flux per lamp (lm)	941	1285	1662
Efficacy (lm/W)	86	79	70
Glare rating	16	17	18


TM30 & CRI diagram



Light distribution & beam diagram




Installation Accessories



10203005 Baseflange 90 Aluminium Matt

10203009 Baseflange 90 White Structure

10203032 Baseflange 90 Black Structure



10204005 Baseflange 90 Tube Aluminium Matt

10204009 Baseflange 90 Tube White Structure

10204032 Baseflange 90 Tube Black Structure

Choose a required accessory