



Date
Customer
Project
Type

Hollow Recessed Trimless Adjustable 115 1x LED 2700K Medium DE Black Structure - Gold Matt



Hollow proposes direct light when open and indirect light when closed. But where does the light come from? Lit or dark, there and not there. A symphony of opposites, Hollow is a downlighter that works with you. Adjustable and versatile. For spaces that welcome intrigue and personality.




Specifications

Material	12170032
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G7
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	92 99 100 100 48
Binning (SDCM)	2
Optic	Lens
Measured beam angle (°)	21.3
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Recessed
Cut-out size (mm)	ø146
Mounting depth (mm)	70.0
Adjustability	H 360° V 90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Secondary Colour & Secondary Finish	Gold, Matt
Gross weight (g)	335.0
Drive current (mA)	350 500
Min. forward voltage (Vf)	14,8 15,2
Max. forward voltage (Vf)	18,0 18,6
Connected load (W)	5,7 8,5
Luminous flux per lamp (lm)	344 464
Efficacy (lm/W)	60 55
Glare rating	13 14

TM30 & CRI diagram



Light distribution & beam diagram



Diagrams

Installation Accessories



10889830 Installation Housing 192x190x130



12292830 Gypsum Fibreboard 190x190



14204030 Ring Recessed Trimless 146 1x

Choose a required accessory