




Date
Customer
Project
Type




Shellby Recessed 1x1 IP55 LED 1800-3000K WD DE Black Structure




Specifications


Material	12180232
Light Source Type	LED
LED Type	BRIDGELUX WARM DIM 12W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	46 81 97 100 22
Binning (SDCM)	3
Light Direction	Down
Optic	Collimator
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	55
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Recessed
Cut-out size (mm)	Ø177
Mounting depth (mm)	100.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	1080.0
Drive current (mA)	350
Min. forward voltage (Vf)	30.6
Max. forward voltage (Vf)	37.0
Connected load (W)	12.0
Luminous flux per lamp (lm)	211
Efficacy (lm/W)	17
Glare rating	28

Shellby's light is the Sun by day, and the Moon by night. Like the Sun, it brings powerful, general light that indisputably brightens your space, and energises you for daily activities. Like the Moon, it watches, with softer light that inspires calm and warmth. A clash of functions, all in one.


TM30 & CRI diagram

Light distribution & beam diagram


Decorative Accessories


12183082 Skin Shellby Bronze Anodised
12183041 Skin Shellby Champagne Anodised
12183042 Skin Shellby Gold Anodised
12183092 Skin Shellby Pearly White Matt
12183084 Skin Shellby Silver Bronze Anodised

Installation Accessories


12182030 Installation Housing 280x350x100x380



12293030 Gypsum Fibreboard 290x280

Choose a required accessory