


|         | _ |
|---------|---|
| ate     |   |
| ustomer |   |
| roject  |   |
| уре     | _ |
|         |   |

FFD\_Trapz Wall Up/Down 2x LED 2700K Trailing Edge DI Bronze Brushed Anodised - Aluminium Anodised



With their indirect lighting and subtle shadow effects, wall fixtures are undoubtedly atmosphere creators. Trapz, our organic interpretation inspired by a trapezium, is no different. The flattened cylinder has been finished with two oblique openings, which allow you to see the contrasting interior of the luminaire and immediately create an unusual chiaroscuro effect.



## Specifications


| specifications                      |                          |
|-------------------------------------|--------------------------|
| Material                            | 12590299                 |
| Light Source Type                   | LED                      |
| LED Type                            | BRIDGELUX V8G8           |
| LED technology                      | LED COB                  |
| CRI                                 | Min. 90                  |
| Colour Temperature                  | 2700K                    |
| Lifetime                            | L90B10 @50,000 Hours     |
| Lamp Included                       | Yes                      |
| Number of Light<br>Sources          | 2                        |
| CIE flux code                       | 69 92 98 50 58           |
| Binning (SDCM)                      | 2                        |
| Light Direction                     | Up/Down                  |
| Input Voltage                       | 230V                     |
| Luminaire power (W)                 | 12.0                     |
| Electrical Class                    | 1                        |
| IP Rating                           | 20                       |
| Glow wire rating (°C)               | 960                      |
| Dimming Protocol                    | Trailing Edge            |
| Indoor/Outdoor                      | Indoor                   |
| Application                         | Wall                     |
| Mounting                            | Surface                  |
| Adjustability                       | Not Applicable           |
| Distance to Lighted<br>Object (m)   | 0,1                      |
| Primary Colour &<br>Primary Finish  | Bronze, Brushed Anodised |
| Secondary Colour & Secondary Finish | Aluminium, Anodised      |
| Gross weight (g)                    | 1181.0                   |
| Delivered lumens (Im)               | 765                      |
| Efficacy (Im/W)                     | 63                       |
| Glare rating                        | 17                       |
|                                     |                          |



Diagrams

## TM30 & CRI diagram





Light distribution & beam diagram

