

|          |
|----------|
| Date     |
| Customer |
| Project  |
| Type     |

*Trapz Wall Up/Down 2x LED 2700K DALI DI Bronze Brushed Anodised - Black Matt*



With their indirect lighting and subtle shadow effects, wall fixtures are undoubtedly atmosphere creators. Trapz, our organic interpretation inspired by a trapezium, is no different. The flattened cylinder has been finished with two oblique openings, which allow you to see the contrasting interior of the luminaire and immediately create an unusual chiaroscuro effect.



### Specifications

|                                     |                          |
|-------------------------------------|--------------------------|
| Material                            | 12592010                 |
| Light Source Type                   | LED                      |
| LED Type                            | BRIDGELUX V8G8           |
| LED technology                      | LED COB                  |
| CRI                                 | Min. 90                  |
| Colour Temperature                  | 2700K                    |
| Lifetime                            | L90B10 @50,000 Hours     |
| Lamp Included                       | Yes                      |
| Number of Light Sources             | 2                        |
| CIE flux code                       | 69 92 98 50 58           |
| Binning (SDCM)                      | 2                        |
| Light Direction                     | Up/Down                  |
| Input Voltage                       | 230V                     |
| Luminaire power (W)                 | 12.0                     |
| Electrical Class                    | I                        |
| IP Rating                           | 20                       |
| Glow wire rating (°C)               | 960                      |
| Dimming Protocol                    | DALI                     |
| DALI Standard                       | DALI-2                   |
| Indoor/Outdoor                      | Indoor                   |
| Application                         | Wall                     |
| Mounting                            | Surface                  |
| Adjustability                       | Not Applicable           |
| Distance to Lighted Object (m)      | 0,1                      |
| Primary Colour & Primary Finish     | Bronze, Brushed Anodised |
| Secondary Colour & Secondary Finish | Black, Matt              |
| Gross weight (g)                    | 1196.0                   |
| Luminous flux per lamp (lm)         | 564                      |
| Efficacy (lm/W)                     | 47                       |
| Glare rating                        | 16                       |

**TM30 & CRI diagram**



**Light distribution & beam diagram**



Diagrams