


| |
|----------|
| Date |
| Customer |
| Project |
| Type |

FFD_Split Wall Up/Down S 1x LED 2700K Trailing Edge DI White Structure - Black Matt

Split is the result of improved folding techniques. A wall-mounted up- and downlighter consisting of a single folded plate with a fine slit from which the light radiates. Split's asymmetrical design makes it ideal for areas that would benefit from atmospheric lighting, such as living rooms, bedrooms or hallways. Available with a white or black structure and a white, black or gold interior that ensures a warm glow.



Specifications

| | |
|-------------------------------------|----------------------|
| Material | 12600029 |
| Light Source Type | LED |
| LED Type | ACRICHE |
| LED technology | LED PCB |
| CRI | Min. 90 |
| Colour Temperature | 2700K |
| Lifetime | L80B20 @50,000 Hours |
| Lamp Included | Yes |
| Number of Light Sources | 1 |
| Binning (SDCM) | 3 |
| Light Direction | Up/Down |
| Input Voltage | 230V |
| Luminaire power (W) | 4.5 |
| Electrical Class | I |
| IP Rating | 20 |
| Glow wire rating (°C) | 960 |
| Dimming Protocol | Trailing Edge |
| Indoor/Outdoor | Indoor |
| Application | Wall |
| Mounting | Surface |
| Adjustability | Not Applicable |
| Distance to Lighted Object (m) | 0,1 |
| Primary Colour & Primary Finish | White, Structure |
| Secondary Colour & Secondary Finish | Black, Matt |
| Gross weight (g) | 735.0 |
| Luminous flux per lamp (lm) | 32 |
| Efficacy (lm/W) | 7 |
| Glare rating | 22 |

TM30 & CRI diagram



Light distribution & beam diagram

