


Date
Customer
Project
Type

FFD_Lotis Square Recessed 1x M-LED DE Black Matt

Lotis Square is a compact, square version of our successful Lotis Round series. The bulb sits deep in a conical cup, making it less visible. An IP variant for use in damp rooms and environments is also available. Then, there is Lotis Square with LED, using our M-LED 50 module. This one allows you to choose from a large range of light colours and three different beam angles (spot, medium or flood).



Specifications

Specifications

Material	12619002
Light Source Type	M-LED
Lifetime	L80B20 @50,000 Hours
Lamp Included	No
Number of Light Sources	1
Light Direction	Down
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Recessed
Cut-out size (mm)	L 78 W 78
Mounting depth (mm)	95.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Matt
Gross weight (g)	127.0
Drive current (mA)	350
Luminous flux per lamp (lm)	409
Efficacy (lm/W)	66
Remark	<ul style="list-style-type: none"> This is not a complete product. Light module required.

M-LED Module




- **14060005** M-LED Module 50 1x LED 2700K Spot DE Aluminium Brushed Anodised
- **14060105** M-LED Module 50 1x LED 2700K Medium DE Aluminium Brushed Anodised
- **14060205** M-LED Module 50 1x LED 2700K Flood DE Aluminium Brushed Anodised
- **14060305** M-LED Module 50 1x LED 3000K Spot DE Aluminium Brushed Anodised
- **14060405** M-LED Module 50 1x LED 3000K Medium DE Aluminium Brushed Anodised
- **14060505** M-LED Module 50 1x LED 3000K Flood DE Aluminium Brushed Anodised
- **14060905** M-LED Module 50 1x LED 4000K Spot DE Aluminium Brushed Anodised
- **14061005** M-LED Module 50 1x LED 4000K Medium DE Aluminium Brushed Anodised
- **14061105** M-LED Module 50 1x LED 4000K Flood DE Aluminium Brushed Anodised
- **14061205** M-LED Module 50 1x LED 1800-3000K WD Spot DE Aluminium Brushed Anodised
- **14061305** M-LED Module 50 1x LED 1800-3000K WD Medium DE Aluminium Brushed Anodised
- **14061405** M-LED Module 50 1x LED 1800-3000K WD Flood DE Aluminium Brushed Anodised

Installation Accessories



10889830 Installation Housing 192x190x130



12291130 Plaster Kit 190x190 - 78x78 1x

■ Choose a required accessory