


Date
Customer
Project
Type

Medard Track 230V Adjustable 70 1x LED 3000K Medium Trailing Edge DI Black Structure




The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.




Specifications

Material	12735132
Light Source Type	LED
LED Type	BRIDGELUX VERO13
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 88
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	25.0
Input Voltage	230V
Luminaire power (W)	13.0
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Ceiling
Adjustability	H 355° V 360°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	940.0
Luminous flux per lamp (lm)	920
Efficacy (lm/W)	70
Glare rating	16
Remark	<ul style="list-style-type: none"> • 4000K on request • This is not a complete product. Track 230V system required.

TM30 & CRI diagram



Light distribution & beam diagram



Diagrams